

Lamps

PRO-TUBOLED T5 AC 150cm 3000K 25W G5

MC21609



PRO-TUBOLED T5 AC 150cm 3000K 25W G5

	MC21609
Nominal voltage	220 - 240 V
Nominal current	155 - 155 mA
Power factor	0.7
Lamp power	25 - 25 W
Voltage type	AC
Suitable for electronic ballast	No
Suitable for magnetic ballast	No
Colour rendering index CRI	80-89
Lamp shape	Tube, single-ended
Filament lamp	No
Material of light bulb	Glass
Type of glass/cover	Opal
Colour of light according to EN 12464-1	Warm white < 3300 K
Socket	G5
Colour	White
Colour temperature	3000 - 3000 K
Housing colour	White
Beam angle	160 - 160 °
Colour consistency (McAdam ellipse)	SDCM6
Dimmable	No
Dimming phase cut-off (trailing edge)	No
Dimming phase cut-on (leading edge)	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	No
Diameter	16 mm
Length	1500 mm
Degree of protection (IP)	IP20
Energy efficiency class according to EU regulation 2019/2015	E
Lamp designation	T5
Weighted energy consumption in 1000 hours	25 kWh
Average nominal lifetime	40000 h
Remote operation possible	No
With movement sensor	No

PRO-TUBOLED T5 AC 150cm 3000K 25W G5

	MC21609
With remote control	No
With twilight switch	No
Photobiological safety according to EN 62471	RG0
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Brand	MARINO CRISTAL
Art. N°	MC21609
Sales unit	pc
EAN PCE	8012878216096
EAN QTY PCE	1
Intrastat code	85308000