

Lamps

ECO TUBILED T8 120 lm/W PF 0.50 - AC180-264 V - 9 W - 1080
lm - 6000

MC21628



ECO TUBILED T8 120 lm/W PF 0.50 - AC180-264 V - 9 W - 1080 lm - 6000 K - G13 - beam 270° - 600 mm

	MC21628
Nominal voltage	180 - 264 V
Nominal current	78 - 78 mA
Power factor	0.5
Lamp power	9 - 9 W
Voltage type	AC
Suitable for electronic ballast	No
Suitable for magnetic ballast	No
Luminous flux	1080 - 1080 lm
Rated luminous flux according to IEC 62612	1080 lm
Lamp efficacy	120 lm/W
Colour rendering index CRI	80-89
Lamp shape	Tube, double-ended
Filament lamp	No
Material of light bulb	Glass
Type of glass/cover	Opal
Colour of light according to EN 12464-1	Neutral white 3300-5300 K
Socket	G13
Colour	White
Colour temperature	4000 - 4000 K
Housing colour	White
Beam angle	160 °
Colour consistency (McAdam ellipse)	SDCM6
Dimmable	No
Dimming phase cut-off (trailing edge)	No
Dimming phase cut-on (leading edge)	No
Dimming Touch and Dim	No
Dimming Zigbee	No

ECO TUBILED T8 120 lm/W PF 0.50 - AC180-264 V - 9 W - 1080 lm - 6000

	MC21628
Dimming Bluetooth	No
Dimming Wi-Fi	No
Diameter	26 mm
Length	600 mm
Degree of protection (IP)	IP20
Energy efficiency class according to EU regulation 2019/2015	E
Lamp designation	T8
Weighted energy consumption in 1000 hours	9 kWh
Average nominal lifetime	20000 h
Remote operation possible	No
With movement sensor	No
With remote control	No
With twilight switch	No
Photobiological safety according to EN 62471	RG0
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Brand	MARINO CRISTAL
Art. N°	MC21628
Sales unit	pc
EAN PCE	8012878216287
EAN QTY PCE	1
Intrastat code	85395200