

DICROICALED TRP DIMMABLE



Code	21716
Lighting technology used:	LED
Non-directional or directional (NDLS / DLS):	DLS
Light source cap-type (or other electric interface):	GU10
Mains or non-mains (MLS / NMLS):	MLS
Dimmable:	yes
On-mode power (Pon), expressed in W	7,5 (W)
Energy consumption (kWh/1000 h)	7 (kWh/1000h)
Energy efficiency class	F
Useful luminous flux (Φuse)	610 in narrow cone (90°)
Correlated colour temperature K	2700

Height	56 (mm)	
Width	50 (mm)	
Depth	50 (mm)	
Claim of equivalent powerc	yes	
If yes, equivalent power (W)	83 (W)	
Chromaticity coordinates (x and y)		
	X	0,456
	Y	0,416
Peak luminous intensity (cd)	674 (cd)	
Beam angle in degrees, or the range of beam angles that can be set	60 (°)	
R9 colour rendering index value	9	
Survival factor	0,9	
Lumen maintenance factor	0,96	
displacement factor (cos φ1)	0,5	
Colour consistency in McAdam ellipses	5	
Flicker metric (Pst LM)	1	
Stroboscopic effect metric (SVM)	0,4	



MARINO CRISTAL SPA

Via Guardia del Consiglio, 29/31

47899 - Serravalle

REPUBBLICA DI SAN MARINO

TEL +378 0549 901188

FAX +378 0549 900612

www.marinocrystal.com

marinocrystal@marinocrystal.com

