

# DICRO\_PRECISE 35MM DIMMABLE



Code	21719	Depth	35 (mm)
Lighting technology used:	LED	L70B50	40000 hours
Non-directional or directional (NDLS / DLS):	DLS	Claim of equivalent powerc	-
Light source cap-type (or other electric interface):		yes	
Mains or non-mains (MLS / NMLS):	MLS	X	0,458
Dimmable:	only with specific dimmers	Y	0,410
On-mode power (Pon), expressed in W	3,5 (W)	Parameters for directional light sources:	
Energy consumption (kWh/1000 h)		Peak luminous intensity (cd)	1100 (cd)
A		Beam angle in degrees, or the range of beam angles that can be set	24 (°)
Useful luminous flux (Φuse)		Parameters for LED and OLED light sources:	(°)
Correlated colour temperature K		Lumen maintenance factor	0,96
		Parameters for LED and OLED mains light sources:	
		displacement factor (cos φ1)	0,7
		Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattaged	-
		Colonna1	
		Total calculations performed with the parameters, including the detemination of the energy efficiency class	
		factors total mains (FTM)	1,176



MARINO CRISTAL SPA

Via Guardia del Consiglio, 29/31

47899 - Serravalle

REPUBBLICA DI SAN MARINO

TEL +378 0549 901188

FAX +378 0549 900612

www.marinocrystal.com

marinocrystal@marinocrystal.com

