






PRO PAR30LED ALU

A+






PAR30LED ALU

codice	W	W	V	attacco	colore	lumen360°	lumen90°	fascio	imballo
code	W	W	V	base	colour	lumen360°	lumen90°	beam	packing
21347	10	91(ERP)	220-240	E27	3000°K	800	780	40°	6/24



PRO PAR38LED ALU

A+







PAR38LED ALU

codice	W	W	V	attacco	colore	lumen360°	lumen90°	fascio	imballo
code	W	W	V	base	colour	lumen360°	lumen90°	beam	packing
21348	15	152(ERP)	220-240	E27	3000°K	1400	1300	40°	6/24



PRO PAR30LED ALU DIMMERABILE

A+

PAR30LED ALU DIMMERABILE

codice	W	W	V	attacco	colore	lumen360°	lumen90°	fascio	imballo
code	W	W	V	base	colour	lumen360°	lumen90°	beam	packing
21350	10	91(ERP)	220-240	E27	3000°K	800	780	40°	6/24







- Dimmerabile con la maggior parte dei dimmers in commercio. Dimmerabilità garantita con i dimmers per lampade LED.

Dimmable with most of the dimmers available on the market. Dimmability guaranteed with dimmers for LED bulbs.



PRO PAR38LED ALU DIMMERABILE

A+

PAR38LED ALU DIMMERABILE

codice	W	W	V	attacco	colore	lumen360°	lumen90°	fascio	imballo
code	W	W	V	base	colour	lumen360°	lumen90°	beam	packing
21351	15	152(ERP)	220-240	E27	3000°K	1400	1300	40°	6/24

- Dimmerabile con la maggior parte dei dimmers in commercio. Dimmerabilità garantita con i dimmers per lampade LED.

Dimmable with most of the dimmers available on the market. Dimmability guaranteed with dimmers for LED bulbs.

