

STD R39LED

A+



3W EPISTAR
SDCR (L6)
CRI >80
PF >0,4
RESTART
15000h
LSP
0.85
20000
Hg
3
LONG LIFE
35000



39mm
67mm

R39LED

codice	W	V	attacco	colore	lumen360°/cd	lumen90°	fascio	imballo
code	W	V	base	colour	lumen360°/cd	lumen90°	beam	packing
21232	3	220-240	E14	3000°K	250/69	240	120°	10/100

STD R63LED EVO ALTA_EFFICIENZA/HIGH EFFICIENCY

A+



7W EPISTAR
SDCR (L6.5)
CRI >80
PF >0,5
RESTART
15000h
LSP
0.85
20000
Hg
3
LONG LIFE
35000



63mm
105mm

R63LED EVO

codice	W	V	attacco	colore	lumen360°/cd	lumen90°	fascio	imballo
code	W	V	base	colour	lumen360°/cd	lumen90°	beam	packing
21055	7	220-240	E27	3000°K	690/167	660	120°	10/100

STD R50LED EVO

A+



5W EPISTAR
SDCR (L6.5)
CRI >80
PF >0,5
RESTART
15000h
LSP
0.85
20000
Hg
3
LONG LIFE
35000



50mm
85mm

R50LED EVO

codice	W	V	attacco	colore	lumen360°/cd	lumen90°	fascio	imballo
code	W	V	base	colour	lumen360°/cd	lumen90°	beam	packing
21141	5	220-240	E14	3000°K	400/130	380	120°	10/100

STD R80LED EVO ALTA_EFFICIENZA/HIGH EFFICIENCY

A+



9W EPISTAR
SDCR (L6.5)
CRI >80
PF >0,5
RESTART
15000h
LSP
0.85
20000
Hg
3
LONG LIFE
35000



80mm
116mm

R80LED EVO

codice	W	V	attacco	colore	lumen360°/cd	lumen90°	fascio	imballo
code	W	V	base	colour	lumen360°/cd	lumen90°	beam	packing
21057	9	220-240	E27	3000°K	910/330	860	120°	10/40