DP S 1200/840 PS SR THRW IP66



REFERENCE
RADAPA5109

BRAND
Radium

EAN
4003556015395

MOQ
1

IP66 IK08

DESCRIPTION

This LED luminaire delivers 5,100 lm of light at a system power of 34 W, with a 4,000 K white light and a luminous efficacy of 150 lm/W. IP66 protection and IK08 impact resistance are complemented by plug-in terminals and through-wiring. Its L70/B50 lifetime is 75,000 hours at 25°C.

ETIM TECHNICAL CHARACTERISTICS

EC000109 - Batten luminaire

With light source	Yes
Material	Plastic
Housing colour	White
Voltage type	AC
Nominal voltage	220 - 240 V
Nominal current	146 - 226 mA
Type of control gear	LED operating device voltage-controlled
With control gear	Yes
Dimmable	No
Dimming with push-button	No
Energy efficiency class of the light source according to EU regulation 2019/2015	D
Containing product according to 2019/2020/EU	Yes
Rated lifetime L70/B50 at 25 °C	75000 h
Degree of protection (IP)	IP66

ETIM TECHNICAL CHARACTERISTICS

EC000109 - Batten luminaire

Protection class according to IEC 61140	II
Impact strength	IK08
With movement sensor	No
Filament test according to IEC 60695-2-11	750 °C - 30 s
With light sensor	No
Max. system power	34 W
Rated luminous flux according to IEC 62722-2- 1	5100 lm
Luminaire efficacy	150 lm/W
Colour of light	White
Colour temperature	4000 K
Power factor	0.9
Colour of light adjustable	No
Luminous flux adjustable	Positions
Beam angle adjustable	No
Width	71 mm
Height/depth	67 mm
Length	1258 mm
Type of wiring	Suitable for loop-through wiring
Connection type	Push-in clamp

PACKAGING

C01

EAN QTY C01	9