DP S 1500/865 PS SR THRW IP66



REFERENCE
RADAPA5112

BRAND
Radium

EAN
4003556415423

MOQ
1

IP66 IK08

DESCRIPTION

For powerful, efficient lighting, this LED luminaire delivers 7,500 lm from a 50 W system, with a luminous efficacy of 150 lm/W. It produces white light at 6,500 K. Its IP66 and IK08 ratings specify its protection and impact resistance. Suitable for through-wiring, it has an integrated, non-replaceable LED source and is not dimmable. Its L70/B50 lifetime is 75,000 hours at 25°C.

ETIM TECHNICAL CHARACTERISTICS

EC000109 - Batten luminaire

Lamp type	LED not exchangeable
With light source	Yes
Lamp holder	None
Material	Plastic
Housing colour	White
Voltage type	AC
Nominal voltage	220 - 240 V
Nominal current	168 - 222 mA
Type of control gear	LED operating device voltage-controlled
With control gear	Yes
Dimmable	No
Dimming with push-button	No
Light distributor	Diffuser lens/optic/panel

ETIM TECHNICAL CHARACTERISTICS

EC000109 - Batten luminaire

Energy efficiency class of the light source according to EU regulation 2019/2015	D
Containing product according to 2019/2020/EU	Yes
Rated lifetime L70/B50 at 25 °C	75000 h
Degree of protection (IP)	IP66
Protection class according to IEC 61140	II
Impact strength	IK08
Emergency power supply system	None
With movement sensor	No
Filament test according to IEC 60695-2-11	750 °C - 30 s
With light sensor	No
Max. system power	50 W
Rated luminous flux according to IEC 62722-2- 1	7500 lm
Luminaire efficacy	150 lm/W
Colour of light	White
Colour temperature	6500 K
Colour rendering index CRI	80-89
Power factor	0.9
Colour of light adjustable	No
Luminous flux adjustable	Positions
Beam angle adjustable	No
Width	71 mm
Height/depth	67 mm
Length	1558 mm
Type of wiring	Suitable for loop-through wiring
Connection type	Push-in clamp