SF E 360 23.5W CCT IP44

REFERENCE
RASFEA5098

BRAND
Radium

EAN
4003556415164

MOQ
1

IP44 IK03

DESCRIPTION

For adaptable direct lighting, this 23.5 W LED luminaire offers a colour temperature selectable in steps from 3,000 K to 4,000 K. Its 2,050 lm light output supports functional illumination, while IP44 protection on the front is suited to environments where this level of protection is required. The white fitting is suitable for surface mounting on a wall or ceiling. Its integrated LED light source is non-replaceable and has an L70/B50 lifetime of 30,000 hours.

ETIM TECHNICAL CHARACTERISTICS

EC002892 - Ceiling-/wall luminaire

Suitable for wall mounting	Yes
Suitable for suspended mounting	No
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	No
Suitable for surface mounting	Yes
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Plastic
Housing colour	White
Material cover	Plastic matt/satinized
Type of grid	None
Voltage type	AC
Nominal voltage	220 - 240 V

ETIM TECHNICAL CHARACTERISTICS

EC002892 - Ceiling-/wall luminaire

Nominal current	188 mA
Type of control gear	LED operating device voltage-controlled
With control gear	Yes
Dimmable	No
Dimming with push-button	No
Light distributor	Diffuser lens/optic/panel
Beam angle	Open beam/diffuse
Light outlet	Direct
Rated lifetime L70/B50 at 25 °C	30000 h
Degree of protection (IP), rear side	Other
Degree of protection (IP), front side	IP44
Max. number of luminaires per miniature circuit breaker B16 (MCB)	42
Max. number of luminaires per miniature circuit breaker C16 (MCB)	67
Impact strength	IK03
Protection class according to IEC 61140	I
Emergency power supply system	None
Suitable for emergency lighting	No
With movement sensor	No
With light sensor	No
Filament test according to IEC 60695-2-11	650 °C - 30 s
Luminaire efficacy	87 lm/W
Max. system power	23.5 W
Rated luminous flux according to IEC 62722-2- 1	2050 lm
Colour of light	White
Colour temperature	3000 - 4000 K
Flickering value Pst LM	1
Power factor	0.7
Stroboscope effect value SVM	0.4
Width	360 mm

ETIM TECHNICAL CHARACTERISTICS

EC002892 - Ceiling-/wall luminaire

Height/depth	100 mm
Length	360 mm
Outer diameter	360 mm
Type of wiring	Ending
Connection type	Push-in clamp
Photobiological safety according to EN 62471	RG0
Unified Glare Ratio (UGR)	28
Colour of light adjustable	Positions
Luminous flux adjustable	No
Beam angle adjustable	No