SF E 360 24.5W CCT IP44 SENSOR*

REFERENCE
RASFEA5099

BRAND
Radium

EAN
4003556015173

MOQ
1

IP44 IK03

DESCRIPTION

This 24.5 W LED luminaire delivers 2,050 lm for effective illumination. It includes a motion detector and a light sensor, with a choice of 3,000 K or 4,000 K colour temperature. Rated IP44, it is suitable for surface mounting on walls or ceilings. Its L70/B50 lifetime is 30,000 hours.

ETIM TECHNICAL CHARACTERISTICS

EC002892 - Ceiling-/wall luminaire

Suitable for wall mounting	Yes
Suitable for suspended mounting	No
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	No
Suitable for surface mounting	Yes
Suitable for light line configuration	No
Suitable for clamp-mounting	No
Lamp type	LED not exchangeable
With light source	Yes
Lamp holder	None
Housing material	Plastic
Housing colour	White
Material cover	Plastic matt/satinized
Type of grid	None

ETIM TECHNICAL CHARACTERISTICS

EC002892 - Ceiling-/wall luminaire

Voltage type	AC
Nominal voltage	220 - 240 V
Nominal current	195 mA
Type of control gear	LED operating device voltage-controlled
With control gear	Yes
Exchangeable control gear	No
Dimming with push-button	No
Light distributor	Diffuser lens/optic/panel
Light distribution	Symmetric
Beam angle	> 80° - Extreme wide beam
Light outlet	Direct
Rated lifetime L70/B50 at 25 °C	30000 h
Degree of protection (IP), front side	IP44
Max. number of luminaires per miniature circuit breaker B16 (MCB)	64
Impact strength	IK03
Protection class according to IEC 61140	I
Emergency power supply system	None
Suitable for emergency lighting	No
With movement sensor	Yes
With light sensor	Yes
Filament test according to IEC 60695-2-11	650 °C - 30 s
Luminaire efficacy	83 lm/W
Max. system power	24.5 W
Rated luminous flux according to IEC 62722-2- 1	2050 lm
Colour of light	White
Colour temperature	3000 - 4000 K
Flickering value Pst LM	1
Power factor	0.7
Stroboscope effect value SVM	0.4

ETIM TECHNICAL CHARACTERISTICS

EC002892 - Ceiling-/wall luminaire

Width	360 mm
Height/depth	100 mm
Length	360 mm
Outer diameter	360 mm
Type of wiring	Ending
Connection type	Push-in clamp
Photobiological safety according to EN 62471	RG0
Unified Glare Ratio (UGR)	28
Colour of light adjustable	Positions
Luminous flux adjustable	No
Beam angle adjustable	No
Operation by Bluetooth	No
Compatible with Casambi	No

PACKAGING

C01

EAN QTY C01	6