# SF S 450 36W PS CCT IP54



REFERENCE
**RASFSA5128**

BRAND
**Radium**

EAN
**4003556015555**

MOQ
**1**

IP54 IK10

**DESCRIPTION**

This LED luminaire delivers powerful, even lighting for surface mounting on a wall or ceiling. It produces 4,680 lm from a 36 W system, with an efficacy of 130 lm/W, and its colour temperature can be selected in steps from 3,000 to 6,000 K. A very wide beam of over 80° and a colour rendering index of 90–100 support high-quality illumination. The white plastic housing has IP54 protection on the rear and IK10 impact resistance. Its L70/B50 lifetime is 70,000 hours, and the through-wiring arrangement supports loop-in/loop-out installation.

## ETIM TECHNICAL CHARACTERISTICS

EC002892 - Ceiling-/wall luminaire

| | |
|---|---|
| **Suitable for wall mounting** | Yes |
| **Suitable for suspended mounting** | No |
| **Suitable for ceiling mounting** | Yes |
| **Suitable for built-in mounting** | No |
| **Suitable for surface mounting** | Yes |
| **Suitable for light line configuration** | No |
| **Suitable for clamp-mounting** | No |
| **Lamp type** | LED not exchangeable |
| **With light source** | Yes |
| **Lamp holder** | None |
| **Housing material** | Plastic |
| **Housing colour** | White |
| **Type of grid** | None |

## ETIM TECHNICAL CHARACTERISTICS

EC002892 - Ceiling-/wall luminaire

| | |
|---|---|
| **Voltage type** | AC |
| **Nominal voltage** | 220 - 240 V |
| **Nominal current** | 260 mA |
| **Type of control gear** | LED operating device voltage-controlled |
| **With control gear** | Yes |
| **Exchangeable control gear** | No |
| **Dimmable** | No |
| **Dimming with push-button** | No |
| **Light distributor** | Diffuser lens/optic/panel |
| **Beam angle** | > 80° - Extreme wide beam |
| **Energy efficiency class of the light source according to EU regulation 2019/2015** | E |
| **Containing product according to 2019/2020/EU** | Yes |
| **Rated lifetime L70/B50 at 25 °C** | 70000 h |
| **Degree of protection (IP), rear side** | IP54 |
| **Max. number of luminaires per miniature circuit breaker B16 (MCB)** | 29 |
| **Impact strength** | IK10 |
| **Protection class according to IEC 61140** | II |
| **Luminaire with limited surface temperature, sign "D“ according to EN 60598-2-24** | No |
| **Emergency power supply system** | None |
| **Rated ambient temperature according to IEC 62722-2-1** | -20 - 40 °C |
| **Suitable for emergency lighting** | No |
| **Emergency function monitoring system** | None |
| **With movement sensor** | No |
| **With light sensor** | No |
| **Filament test according to IEC 60695-2-11** | 850 °C - 30 s |
| **Luminaire efficacy** | 130 lm/W |
| **Max. system power** | 36 W |
| **Rated luminous flux according to IEC 62722-2- 1** | 4680 lm |

## ETIM TECHNICAL CHARACTERISTICS

EC002892 - Ceiling-/wall luminaire

| | |
|---|---|
| **Colour of light** | White |
| **Colour temperature** | 3000 - 6000 K |
| **Flickering value Pst LM** | 1 |
| **Colour rendering index CRI** | 90-100 |
| **Stroboscope effect value SVM** | 0.4 |
| **Width** | 450 mm |
| **Height/depth** | 70 mm |
| **Length** | 450 mm |
| **Outer diameter** | 450 mm |
| **Type of wiring** | Suitable for loop-through wiring |
| **Connection type** | Push-in clamp |
| **Photobiological safety according to EN 62471** | RG0 |
| **Unified Glare Ratio (UGR)** | 25 |
| **Colour of light adjustable** | Positions |
| **Luminous flux adjustable** | Positions |
| **Beam angle adjustable** | No |

## PACKAGING

**C01**

| | |
|---|---|
| **EAN QTY C01** | 5 |