

## Tools for drilling, turning, milling

Use: bar-turning steel R<450N/mm<sup>2</sup>, low-alloy steel R<750N/mm<sup>2</sup>,  
 "Mid-H

R3000-19



**riss**

Use: bar-turning steel R450N/mm<sup>2</sup>, low-alloy steel R750N/mm<sup>2</sup>, "Mid-Hard" low-alloy steel R950N/mm<sup>2</sup>  
 "Hard" alloy or treated steel R950N/mm<sup>2</sup> Top angle: 118° Angle helix: 30°, Ø-tolerance h8 Neckline

|                              | R3000-19                 |
|------------------------------|--------------------------|
| Suitable for wood            | No                       |
| Suitable for steel           | Yes                      |
| Suitable for stainless steel | Yes                      |
| Suitable for stone           | No                       |
| Suitable for plastic         | No                       |
| Diameter drill               | 19 mm                    |
| Spiral drill                 | Yes                      |
| Shaft diameter               | 19 mm                    |
| Shank shape                  | Cylindrical              |
| Cutting edge length          | 135 mm                   |
| Number of cutting edges      | 2                        |
| Total length                 | 199 mm                   |
| Holding system               | Cylindrical plug-in axle |
| With quick-lock              | No                       |
| Tip angle                    | 118 °                    |
| Cutting direction            | Right                    |
| Cutting material             | HSS                      |

|                |               |
|----------------|---------------|
| Brand          | RISS          |
| Art. N°        | R3000-19      |
| Sales unit     | pc            |
| EAN PCE        | 3253112329003 |
| EAN QTY PCE    | 1             |
| Intrastat code | 82075060      |