

Tools for drilling, turning, milling

Use: free-cutting steel R<450N/mm², low-alloy steel R<750N/mm²,
 "Mid-

R3005V-4



riss

Use: free-cutting steel R450N/mm², low-alloy steel R750N/mm², "Mid-Hard" low-alloy steel R950N/mm² Top
 angle: 118° Helix angle: 30°, Ø-tolerance h8 Neckline at 13 mm from Ø13.5 to Ø20 mm Packing: 1

	R3005V-4
Suitable for wood	No
Suitable for steel	Yes
Suitable for stainless steel	Yes
Suitable for nonferrous metals	Yes
Suitable for cast iron	No
Suitable for plastic	No
Diameter drill	4 mm
Spiral drill	Yes
Shaft diameter	4 mm
Shank shape	Cylindrical
Cutting edge length	43 mm
Number of cutting edges	2
Total length	75 mm
Holding system	Cylindrical plug-in axle
With quick-lock	No
Plug-in axle with flat end	No
With centre drill	No
Double sided drill	No
With cooling channel	No
Tip angle	118 °
Suitable for re boring	No
Cutting direction	Right
Cutting material	HSS

Brand	RISS
Art. N°	R3005V-4
Sales unit	pc
EAN PCE	3253113006040
EAN QTY PCE	1
Intrastat code	82075060