

Tools for drilling, turning, milling

Use: free-cutting steel R<450N/mm², low-alloy steel R<750N/mm²,
"Mid-

R3005V-8



riss

Use: free-cutting steel R450N/mm², low-alloy steel R750N/mm², "Mid-Hard" low-alloy steel R950N/mm² Top
angle: 118° Helix angle: 30°, Ø-tolerance h8 Neckline at 13 mm from Ø13.5 to Ø20 mm Packing: 1

	R3005V-8
Suitable for brick	0
Suitable for wood	No
Suitable for steel	Yes
Suitable for stainless steel	No
Suitable for nonferrous metals	Yes
Suitable for cast iron	Yes
Suitable for stone	No
Suitable for concrete	No
Suitable for tiles	No
Suitable for ceramics	No
Suitable for glass	No
Suitable for plastic	Yes
Diameter drill	8 mm
Spiral drill	Yes
Shaft diameter	8 mm
Shank shape	Cylindrical
Cutting edge length	75 mm
Number of cutting edges	2
Total length	117 mm
Holding system	Cylindrical plug-in axle
With quick-lock	No
Plug-in axle with flat end	No
With centre drill	No
Double sided drill	No
With cooling channel	No
Suitable for re boring	No
Cutting direction	Right
Cutting material	HSS

Use: free-cutting steel R<450N/mm², low-alloy steel R<750N/mm²,
"Mid-

Brand	RISS
Art. N°	R3005V-8
Sales unit	pc
EAN PCE	3253113006088
EAN QTY PCE	1
Intrastat code	82075060