

Tools for drilling, turning, milling

Use: bar-turning steel R<450N/mm², low-alloy steel R<750N/mm²,
"Mid-H

R3075V-5



riss

Use: bar-turning steel R450N/mm², low-alloy steel R750N/mm², "Mid-Hard" low-alloy steel R950N/mm²,
"Hard" alloy or treated steel R950N/mm², Stainless steel, alloy cast iron or gray Top angle: 118°

	R3075V-5
Suitable for brick	0
Suitable for wood	No
Suitable for steel	Yes
Suitable for stainless steel	Yes
Suitable for nonferrous metals	No
Suitable for cast iron	Yes
Suitable for stone	No
Suitable for concrete	No
Suitable for tiles	No
Suitable for ceramics	No
Suitable for glass	No
Suitable for plastic	No
Diameter drill	5 mm
Spiral drill	Yes
Shaft diameter	5 mm
Shank shape	Cylindrical
Cutting edge length	52 mm
Number of cutting edges	2
Total length	86 mm
Holding system	Cylindrical plug-in axle
With quick-lock	No
Plug-in axle with flat end	No
With centre drill	No
Double sided drill	No
With cooling channel	No
Tip angle	135 °
Suitable for re boring	No
Cutting direction	Right
Cutting material	HSS-E

Use: bar-turning steel R<450N/mm², low-alloy steel R<750N/mm²,
"Mid-H

Brand	RISS
Art. N°	R3075V-5
Sales unit	pc
EAN PCE	3253119375508;3253110116681
EAN QTY PCE	1
EAN QTY C01	10
Intrastat code	82075060