

## Tools for drilling, turning, milling

Use: bar-turning steel R<450N/mm<sup>2</sup>, low-alloy steel R<750N/mm<sup>2</sup>,  
"Mid-H

R3075V-6



**riss**

Use: bar-turning steel R450N/mm<sup>2</sup>, low-alloy steel R750N/mm<sup>2</sup>, "Mid-Hard" low-alloy steel R950N/mm<sup>2</sup>,  
"Hard" alloy or treated steel R950N/mm<sup>2</sup>, Stainless steel, alloy cast iron or gray Top angle: 118°

|                                | R3075V-6                 |
|--------------------------------|--------------------------|
| Suitable for brick             | 0                        |
| Suitable for wood              | No                       |
| Suitable for steel             | Yes                      |
| Suitable for stainless steel   | Yes                      |
| Suitable for nonferrous metals | No                       |
| Suitable for cast iron         | Yes                      |
| Suitable for stone             | No                       |
| Suitable for concrete          | No                       |
| Suitable for tiles             | No                       |
| Suitable for ceramics          | No                       |
| Suitable for glass             | No                       |
| Suitable for plastic           | No                       |
| Diameter drill                 | 6 mm                     |
| Spiral drill                   | Yes                      |
| Shaft diameter                 | 6 mm                     |
| Shank shape                    | Cylindrical              |
| Cutting edge length            | 57 mm                    |
| Number of cutting edges        | 2                        |
| Total length                   | 93 mm                    |
| Holding system                 | Cylindrical plug-in axle |
| With quick-lock                | No                       |
| Plug-in axle with flat end     | No                       |
| With centre drill              | No                       |
| Double sided drill             | No                       |
| With cooling channel           | No                       |
| Tip angle                      | 135 °                    |
| Suitable for reboring          | No                       |
| Cutting direction              | Right                    |
| Cutting material               | HSS-E                    |

---

Use: bar-turning steel R<450N/mm<sup>2</sup>, low-alloy steel R<750N/mm<sup>2</sup>,  
"Mid-H

---

|                |               |
|----------------|---------------|
| Brand          | RISS          |
| Art. N°        | R3075V-6      |
| Sales unit     | pc            |
| EAN PCE        | 3253110116780 |
| EAN QTY PCE    | 1             |
| Intrastat code | 82075060      |