



X-Blast 50W: LED floodlight with 3m cable and French plug. 4700lm



PACKING	INNER	MASTER
/	pcs	pcs
Colour box	N/A	2



DATI TECNICI / SPECIFICATION / CARACTÉRISTIQUES / CARACTERISTICAS / SPEZIFIKATIONEN

Power supply:	AC 220-240V ~ 50Hz
Type of power supply:	INTERNAL DRIVER
Batteries included:	NO
Light technology:	2835 SMD LED
Power (W):	50
Kelvin degrees:	6500K
Light beam:	DIFFUSE
Beam angle:	120
LED Life time (hrs):	25000
Materials:	PLASTIC - PC
Dimmable:	NO
Insulation class:	I
Colour:	YELLOW
Switch:	YES
Protection degree (IP):	IP54
Guarantee:	2 YEARS
Product width (mm):	240
Product depth (mm):	217
Product height (mm):	99
Net weight kg):	1,45

DESCRIZIONE / DESCRIPTION / DESCRIPTION / DESCRIPCIÓN / BESCHREIBUNG

Power: X-Blast 50W is a construction site floodlight that mounts Osram LEDs. 50W and 4500 real lumens: a real light on your construction site; aircraft grade aluminum heatsink for better heat dissipation. Diffuser: X-Blast is a floodlight type projector; it therefore serves to illuminate a surface such as a wall or a room; polycarbonate diffuser and 120 ° high performance reflector for a shadowless and homogeneous light; light 6500K. Ideal for construction and craft work, for do-it-yourself or car repairs; outdoors, it is recommended for work on the facades, rescue, road works, but also for camping; you can use it wherever you want intense lighting and protected from water and dust. Equipped with a 3 meter H05RN-3G 1,5mm² cable with CEE 7/7 socket, X-Blast can be installed on any tripod; the adjustable support allows you to adjust the light as you need and to carry the projector anywhere, with a minimum footprint; convenient ON / OFF switch and French service socket to connect a tool or other projector in series. X-Blast is hyper-resistant and is proof against water jets according to the IP54 protection class; the shell is in polycarbonate with PVC reinforcements for better impact resistance (IK08), the glass is shockproof and the power cable is fixed with a special thread in the shell; even in case of rain X-Blast continues to illuminate the surrounding environment without any problem.

DATI LOGISTICI / LOGISTIC INFORMATION / DONNEES LOGISTIQUES / DATOS LOGÍSTICOS / LOGISTISCHE DATEN

Tipologia imballo:	Colour box
Length of the packed product (mm):	260
Packed product width (mm):	126
Height of packed product (mm):	225
Peso prodotto imballato (Kg):	1.61
Master quantity:	2
DEEE (France only):	0.25

