

Luminaire

SMD LED floodlight for indoors or outdoors - 200 W - 15000 lm - 6500

A-IS786



SMD LED floodlight for indoors or outdoors - 200 W - 15000 lm - 6500 K - black

	A-IS786
Suitable for surface mounting	Yes
Suitable for wall mounting	Yes
Adjustability	Not adjustable
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Aluminium
Housing colour	Black
Material cover	Glass transparent
Voltage type	AC
Nominal voltage	220 - 220 V
Type of control gear	LED operating device current-controlled
With control gear	Yes
Light distribution	Symmetric
Beam angle	> 80° - Extreme wide beam
Light outlet	Direct
Energy efficiency class of the light source according to EU regulation 2019/2015	F
Rated lifetime L70/B50 at 25 °C	25000 h
Degree of protection (IP), rear side	EV006421
Degree of protection (IP), front side	IP65
Protection class according to IEC 61140	I
Max. system power	200 W
Colour of light	White
Colour temperature	6500 - 6500 K
Colour rendering index CRI	80-89
Rated luminous flux according to IEC 62722-2- 1	17000 - 17000 lm

SMD LED floodlight for indoors or outdoors - 200 W - 15000 lm - 6500

	A-IS786
Luminous flux adjustable	No
Luminaire efficacy	85 - 85 lm/W
Width	362 mm
Height/depth	304 mm
Conductor cross section	1 mm ²
Connectable conductor cross section	1 - 1 mm ²
Connection type	Free conductor end

Brand	VELAMP
Art. N°	A-IS786
Sales unit	pc
EAN PCE	8003910104594
EAN QTY PCE	1
EAN C01	18003910104591
EAN QTY C01	2
Intrastat code	94054910