






**SPOTEX: 5W ATEX rechargeable spotlight, 300 lm.
With wall charging base**



PACKING	INNER	MASTER
	 pcs	 pcs
White box	N/A	N/A



DATI TECNICI / SPECIFICATION / CARACTÉRISTIQUES / CARACTERISTICAS / SPEZIFIKATIONEN

Product name:	SPOTEX
Power supply:	RECHARGEABLE BATTERIES
Power supply included:	YES
Type of power supply:	AC/DC ADAPTOR
Batteries included:	YES
Battery (type):	18650
Battery (capacity mAh):	Specific model
Battery technology:	LITHIUM-ION
Runtime (hrs):	4
Light technology:	HIGH POWER LED
Power (W):	5
Lumen:	300
Kelvin degrees:	6500K
Light beam:	FOCUS
Range (m):	334
Insulation class:	III
Colour:	Yellow
Switch:	YES
Plug:	Type C/EF - 2 pin (Europlug/FR-DE Hybrid)
Guarantee:	2 ANNI
Product width (mm):	260
Product depth (mm):	150
Product height (mm):	175
Net weight kg):	1,004

DESCRIZIONE / DESCRIPTION / DESCRIPTION / DESCRIPCIÓN / BESCHREIBUNG




Powerful: spotted is a very powerful hand light: 5W (XP-G3 CREE), 300 real lumens; aircraft grade aluminium heatsink for better heat dissipation. Range: 300 m, 30 ° focused light, Velamp high performance reflector. Individual; central LED: up to 50 hours (light 20%). 16 hours for 50% light. 4 hours for 100 ° light; the headlight is equipped with a 3,7V 2Ah 18650 type li-ion battery; recharges in 6 hours; included: 220V adapter, wall charger. ATEX: ATEX zone 0 certificate. Resistant: in polycarbonate and abs; IP64: water resistant.

DATI LOGISTICI / LOGISTIC INFORMATION / DONNEES LOGISTIQUES / DATOS LOGÍSTICOS / LOGISTISCHE DATEN

Packing type:

White box



	Class I Div 1&2 Grp ABCD / Class II Div 1&2 Grp EFG Class III / Temperature Code T4 IP64 File number: 261379
	Gas: II 1G Ex ia op is IIC T4 Ga (Zone 0) Mine: I M1 Ex ia op is I Ma SIRA 17 ATEX 2195X
	Gas: Ex ia op is IIC T4 Ga (Zone 0) Mine: Ex ia op is I Ma IECEx SIR 17.0042X
	0518

