







3kW PTC heater



PACKING	INNER	MASTER
 / 	 pcs	 pcs
<b>Scatola</b>	<b>N/A</b>	<b>N/A</b>



## DATI TECNICI / SPECIFICATION / CARACTÉRISTIQUES / CARACTERISTICAS / SPEZIFIKATIONEN

<b>Product name:</b>	FAN HEATER
<b>Power supply:</b>	220-240v
<b>Batteries included:</b>	Si
<b>Power supply included:</b>	Yes
<b>Type of power supply:</b>	Cavo elettrico 140cm
<b>Power (W):</b>	3000
<b>Materials:</b>	Metal
<b>Insulation class:</b>	I
<b>Power cable length (cm):</b>	140cm
<b>Colour:</b>	Black
<b>Switch:</b>	Y
<b>Protection degree (IP):</b>	20
<b>Accessories included:</b>	Integrated thermostat, Overheating protection
<b>Functions:</b>	1) Fan only 2) Normal power 3) High power
<b>Current (A):</b>	12.5 - 13.6A
<b>Plug:</b>	Type E / F - 2 pin (EU Hybrid)
<b>Setting (W):</b>	25/1500/3000
<b>Timer:</b>	NO
<b>Guarantee:</b>	2 ANNI
<b>Product width (mm):</b>	265
<b>Product depth (mm):</b>	210
<b>Product height (mm):</b>	290
<b>Net weight kg):</b>	2,785
<b>Noise level (dB):</b>	

**DESCRIZIONE / DESCRIPTION / DESCRIPTION / DESCRIPCIÓN / BESCHREIBUNG**

3000W hot air generator; ceramic technology: unlike serpentine models, ceramic models are hot immediately; the "cannon" shape guarantees a better direction to the air flow .Excellent for temporary heating of a 60m3 room; useful for drying plasters. With fan function. Temperature regulation (25/1500 / 3000W), heats 217m3 / h; with safety thermostat (starts at 85 °). Equipped with 140cm cable with CEE 7/7 socket (schuko); hyper resistant metal structure; IPX0; use temperature: -15 ° c / + 25 ° c.

**DATI LOGISTICI / LOGISTIC INFORMATION / DONNEES LOGISTIQUES / DATOS LOGÍSTICOS / LOGISTISCHE DATEN****Packing type:**

Scatola

