

Technical Data Sheet

CODE 16028

CA 150 V0 D

In-line centrifugal fans in self-extinguishing plastic



Certifications



IMQ

IMQ Performance



C Tick Mark

EAC

TECHNICAL AND PERFORMANCE DATA

Absorbed power 1st speed (W)	14	Weight (Kg)	2,6
Absorbed Power max (W)	52	Delivery 1st speed (l/s)	41
Frequency (Hz)	50	Delivery 1st speed (m ³ /h)	150
Insulation Class	II°	Max delivery at max speed (l/s)	128
IP	X4	Max delivery at max speed (m ³ /h)	460
Max ambient temperature for continuous operation (°C)	50	Pressure - 1st speed (mmH2O)	8,4
Max. absorbed Current at max. speed (A)	0,22	Pressure - 1st speed (Pa)	83
Max. absorbed Current at min. speed (A)	0.14	Pressure max - max speed (mmH2O)	31,8
Nominal Diameter (mm)	150	Pressure max - max speed (Pa)	312
Ø Discharge Hole (mm)	147	RPM max	2400
Voltage (V)	220-240	Sound pressure level Lp [dB (A)] 3m - max speed	56

DIMENSIONS



Size A (mm)	300
Size B (mm)	305
Size C (mm)	300
Size D (mm)	147/157
Size E (mm)	30/60
Size F (mm)	30/60

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com

Technical Data Sheet

CODE 16028

CA 150 V0 D


In-line centrifugal fans in self-extinguishing plastic



DESCRIPTION

- Material: self-extinguishing PP thermoplastic resin, rated V0.
- Nominal diameter 150 mm.
- 3 speed fan through TRIO-CA optional control (cod. 12869), consisting of:
 - AC motor with thermal overload cutout and shaft turning in ball bearings,
 - backward curved impeller.
- Operation controllable by remote sensors monitoring: Temperature, Relative Humidity, Smoke and Presence.
- Zinc-coated steel brackets for wall mounting.

CURVES



ACCESSORIES



C 1.5
(COMANDO EL.
1.5 A)
Code 12966



C 2.5
(COMANDO EL.
2.5 A)
Code 12967



KIT SCB
(TRASF.E.C.)
Code 22481



CA-MU (STAFFE
DI SOSTEGNO)
Code 22674

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)
Pre & Post Vendita: fax +39 02 90699302
Email prevendita: prevendita@vortice-italy.com