

Technical Data Sheet

CODE 25045

DEPURO 45 H

Air cleaners with electrostatic filter




Certifications



TECHNICAL AND PERFORMANCE DATA

Absorbed Current max (A)	0,27	Delivery 1st speed (m ³ /h)	30
Absorbed Power max (W)	30	Max delivery at max speed (m ³ /h)	60
Frequency (Hz)	50	Sound power Lw [dB(A)] - min speed	41
Insulation Class	II°	Sound power Lw [dB(A)] - max speed	53
Number of speeds	3	Sound power Lw [dB(A)] - mid speed	50
Voltage (V)	230	Sound pressure level Lp [dB (A)] 3m - max speed	39,1
Weight (Kg)	4,0	Sound pressure level Lp [dB (A)] 3m - mid speed	35,7
		Sound pressure level Lp [dB (A)] 3m - min speed	27,5

DIMENSIONS



Size A (mm)	358
Size B (mm)	180
Size C (mm)	437
Size D (mm)	315
Size E (mm)	120

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com

Technical Data Sheet

CODE 25045

DEPURO 45 H

Air cleaners with electrostatic filter



DESCRIPTION

- Upper casing, filter cover, sides, grille and base moulded from impact-resistant thermoplastic material, colour grey.
- 3 speed motor with thermal overload protection and double extension shaft turning in self-lubricating bushings, coupled to 2 impellers made of thermoplastic material; vibration eliminated by rubber dampers located between motor and mounting.
- Washable polyester-polyurethane prefilter.
- HEPA H10 filter
- Electrostatic double layer filter impregnated with activated carbon.
- Ionizing electrodes selectable by way of dedicated switch.
- On/off switch.
- Fan speed controlled by 3-position rotary switch.
- Base interchangeable with one side to allow floor-standing operation.
- Power cord with moulded plug.
- IMQ safety certification.

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com