

Technical Data Sheet

CODE 40956

E 404 T

Low-pressure plate axial fans





UL



TECHNICAL AND PERFORMANCE DATA

Absorbed Current at 220 V (A)	0,60	Max Temperature of Exhaust Air (Continuous Operation)	70
Absorbed Current at 240 V (A)	0,65	Motor IP protection	44
Absorbed Current at 380 V (A)	0,35	Nominal Diameter (mm)	400
Absorbed Current at 415 V (A)	0,38	Number of Poles	4
Absorbed Current max (A)	0,65	Voltage (V)	220/380 240/415
Absorbed power at 220-380 V (W)	190	Weight (Kg)	6,5
Absorbed power at 240-415 V (W)	200	Delivery max (l/s)	889
Absorbed Power max (W)	200	Delivery max (m³/h)	3200
Frequency (Hz)	50	Pressure max (mmH2O)	17,7
Insulation Class	1°	Pressure max (Pa)	174
Max ambient temperature for continuous operation (°C)	70	RPM	1400
		Sound Pressure level Lp [dB (A)] 3m	60

DIMENSIONS



Diametro Ø (mm)	400
Size A (mm)	510
Size B (mm)	430
Size C (mm)	274
Size D (mm)	Ø
	410
Size D3 (mm)	Ø
	400
Size E (mm)	90
Size F (mm)	12
Size G (mm)	15

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com

Technical Data Sheet

CODE 40956

E 404 T

Low-pressure plate axial fans



DESCRIPTION

- Nominal diameter 400 mm
- Wall-mounting panel manufactured from phosphated pressed steel, long-term resistance to atmospheric agents.
- Ventilation port fashioned in one piece with the panel and gauged to UNI ISO 13857 standard
- Protective grille (in accordance with UNI ISO 13857 standard) combining the function of motor bracket, made of electrically welded metal, maintenance and cleaning of the fan.
- 1 speed asynchronous three-phase AC motor with shaft turning in double shielded ball bearings, insulation class F.
- Dynamically balanced (UNI ISO 1940 - Balancing class 6.3), optimized to deliver maximum performance and low noise levels, and resistance to atmospheric agents.
- Vortice speed controller.


ACCESSORIES



IRT 15
Code 12923



PGR 400
(PERSIANA
GRAVITA')
Code 50450



TRA 400
(TELAIO CON
RETE ANTINF.)
Code 51450



DPU 400
(DISTANZIATORE)
Code 52451

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com