

Technical Data Sheet

CODE 45302

VORT QBK POWER 9/7 1V 0,55



Belt driven cabinet fans




CE



TECHNICAL AND PERFORMANCE DATA

Frequency (Hz)	50	Number of Phases (Ph)	3
Max ambient temperature for continuous operation (°C)	40	Number of speeds	1
Motor Class	F	Voltage (V)	230/400
Motor IP protection	55	Delivery max (l/s)	694
Nominal Current (A)	1,6	Delivery max (m³/h)	2500
Nominal Power (W)	550	RPM max	1520
		Sound pressure level air extraction Lp [dB (A)] 1m - max speed	72

DIMENSIONS



Size A (mm)	790
Size B (mm)	600
Size C (mm)	600
Size D (mm)	235
Size E (mm)	265

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com

Technical Data Sheet

CODE 45302

VORT QBK POWER 9/7 1V 0,55






Belt driven cabinet fans

DESCRIPTION

• Cabinet fabricated from extruded aluminium angle sections (UNI 9006) and zinc-coated sheet metal panels, insulated with polyethylene

• 1 speed three-phase AC motor, coupled by way of belt and pulley drive to a forward-bladed double inlet centrifugal impeller.

ACCESSORIES



← QBK ABC 7/7-
9/9
(MANICOTTO
CON RETE)
Code 24200

QBK RRC
POWER 9/7-9/9
(TETTUCCIO)
Code 24215

QBK VCD
POWER 9/7-9/9
(SERRANDA+COMANDO)
Code 24222

→ QBK IG POWER
9/7-9/9
(GRIGLIA
ASPIRAZ.)
Code 24230

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com