

Technical Data Sheet

CODE 45386

VORT NRG 4500 EC

Heat recovery units equipped with static heat exchangers




Certifications



TECHNICAL AND PERFORMANCE DATA

Filter class for extract air	G4	Nominal Diameter (mm)	500
Filter class for supply air	F7	Number of Phases (Ph)	3+N
Frequency (Hz)	50	Protection current	7,7
Max ambient temperature for continuous operation (°C)	40	Voltage (V)	400
Motor Class	B	Weight (Kg)	550
Motor IP protection	54	Delivery max (m ³ /h)	5000
Motor Power (W)	2500X2	Sound power level - radiated Lw [dB(A)]	61

DIMENSIONS



Size A (mm)	2625
Size B (mm)	1515
Size C (mm)	805
Size D (mm)	405
Size E (mm)	705
Size F (mm)	655
Size F1 (mm)	1520
Size F2 (mm)	450
Vents diameter Ø A (mm)	500

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com

Technical Data Sheet

CODE 45386

VORT NRG 4500 EC

Heat recovery units equipped with static heat exchangers



DESCRIPTION

- Frames consisting of rounded aluminium profiles with built-in, polyamide made, spacers for class TB2 thermal break; corners made of reinforced polyamide; double skin (sandwich), 10/10 panels (inner side with galvanized steel sheet, outer side with pre-laquered metal sheet (RAL 7035) with protective film); insulation through 50 mm high density (M0) mineral wool.
- 2 EC motors, independently adjustable, external rotor type, integrating safety thermal cut-outs, with backward curved impellers directly driven by ball bearings; 2 speeds adjustable during the installation.
- Air-to-air, counter cross-flow, aluminium made heat exchanger whose high performance, certified by Eurovent, exceeds 90% according to EN 308 standard.
- Circular branch connections with lip seals to grant the system air tightness.
- 100% inner automatic by-pass.
- 2 filters, respectively G4 on extracted air (stale) and F7 on (fresh) air supply, both mounted upstream of inner components, on runners fitted with lip seals to ensure effective air tightness.
- Access to filters and inner components by security latch on removable panels.
- Brackets crimped into the structure for fixing to the ground or ceiling/false ceiling.
- Inner slanted tray to assure the proper condensate removal at product horizontally installed.
- A dedicated pressure switch constantly controls the airflow across each fan, which indicates the presence of a fault on any external device which can be connected on the clean contact on board of the machine.
- A podlockable local circuit breaker, mounted on front panel, allows to stop the unit in case of fault.
- Potentiometers to independently adjust each fan speed.

ACCESSORIES



POTI NRG
Code 21039



NRG EC RRC V
4500
Code 21082



NRG EC RRO
4500
Code 21077

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)
Pre & Post Vendita: fax +39 02 90699302
Email prevendita: prevendita@vortice-italy.com