

# Technical Data Sheet

CODE 61750

## NORDIK EVOLUTION R 90/36" BIANCO

Reversible ceiling fans



### Certifications



### TECHNICAL AND PERFORMANCE DATA

Absorbed Current max (A)	0,34	Weight (Kg)	6,4
Absorbed Power max (W)	70	Airflow speed at max speed (m/s)	3,52
Blades diameter	980	Delivery max (m <sup>3</sup> /h)	11592
Frequency (Hz)	50	Delivery max (m <sup>3</sup> /min)	193,20
Insulation Class	I°	RPM	200
Voltage (V)	220-240	Service value (m <sup>3</sup> /min)/W	2,760
		Sound power level Lw [dB(A)]	46,1

#### PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: [prevendita@vortice-italy.com](mailto:prevendita@vortice-italy.com)

# Technical Data Sheet

CODE 61750

## NORDIK EVOLUTION R 90/36" BIANCO

Reversible ceiling fans



### DESCRIPTION

- Nominal diameter of blades 900 mm
- Top and bottom motor covers moulded from heat-resistant and UV-resistant thermoplastic resin (ABS), colour white.
- Wiring connections at end of ceiling rod concealed by domes moulded from impact- and UV-resistant thermoplastic resin (PP).
- Single phase start capacitor motor with external rotor, and shaft turning in ball bearings. Direction of rotation reversible.
- Maximum air flow 11592 m3/h
- 3 galvanized sheet steel blades powder coated with scratch-resistant polyester, colour white.
- Steel ceiling rod with scratch-resistant polyester powder coated finish, colour white, length 375 mm.
- Bag of accessories containing nuts and bolts required for assembly of blades, ceiling hook and rubber anti-vibration washer.
- Factory-prepared to accept 2 specific optional light kits:
  - ? with lamp rated 105 W max, E27 screw fitting
  - ? with 2x15 W max energy saving lamp, E27 screw fitting (mandatory in EU).
- Speed selectable by way of control units or Telenordik 5TR remote control (optional)

### ACCESSORIES



**EVOLUTION  
LIGHT KIT ES**  
Code 22414



**EVOLUTION  
LIGHT KIT**  
Code 22413



**TELENORDIK  
5TR**  
Code 22386



**SCRR5**  
Code 12963

#### PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)  
Pre & Post Vendita: fax +39 02 90699302  
Email prevendita: prevendita@vortice-italy.com