

Technical Data Sheet

CODE 70592

MICROSOL 2000-V0

Compact wall-mounted convector heaters




Certifications



TECHNICAL AND PERFORMANCE DATA

Absorbed Current max (A)	8,7	Insulation Class	I°
Absorbed Power max (W)	2000	IP	X4
Frequency (Hz)	50	Voltage (V)	230
		Weight (Kg)	4,6

DIMENSIONS



Size A (mm)	863
Size B (mm)	258
Size C (mm)	109

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com

Technical Data Sheet

CODE 70592

MICROSOL 2000-V0

Compact wall-mounted convector heaters



DESCRIPTION

- Front and rear panels, top and bottom grilles made of steel with scratch-resistant paint finish, colour grey.
- Ends and section housing controls made of self-extinguishing plastic rated V0, colour grey.
- Metal-clad heating element with aluminium heat sink; 3 heat output settings: 800/1200/2000 W.
- Thermal overload cutout with manual reset.
- Luminous switches for on/off control and selection of heat output settings.
- Manually adjustable room thermostat with antifreeze function guaranteeing automatic activation of the heater whenever ambient temperature drops below 5 °C.
- The product can be connected to an external programmable thermostat
- IMQ safety certification.

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com