Technical Data Sheet

CODE 60624

GORDON EVO 30/12"

Oscillating table and podestal fans





Certifications **C€** ^{CE}




CB TEST REPORT

Technical and performance data

| Frequency (Hz) | 50-60 |
|--------------------------|----------|
| Insulation class | II° |
| Max absorbed current (A) | 0,7 |
| Max absorbed power (W) | 22 |
| Tensione adattatore (V) | 100-240V |
| Voltage (V) | 24 |
| | |

| Max airflow (m³/h) | 2340 |
|---------------------------------------|------|
| Max airflow (m³/min) | 38,7 |
| Max flow speed (m/s) | 2,2 |
| Power in stand-by mode (W) | 0,3 |
| Seasonal electric consumption (kWh/y) | 6,3 |
| Service value (m³/min)/W | 2,1 |
| Sound power at Min speed LWA [dB(A)] | 57 |

Dimensions



| ψ (mm) | 31/ |
|-------------|-------|
| Size A (mm) | Ø |
| | 348 |
| Size B (mm) | 565 |
| Size C (mm) | Ø 330 |
| Size D (mm) | 303 |

PER INFORMAZIONI / FOR INFORMATION

ITALY
Pre Sales:
prevendita@vortice-italy.com
After Sales:
postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF IRELAND
Sales Dept:
sales@vortice.ltd.uk
Technical Dept:
technical@vortice.ltd.uk

OTHER COUNTRIES
Sales Dept:
export@vortice-italy.com
After Sales:
after-sales@vortice-italy.com

Technical Data Sheet

CODE 60624

GORDON EVO 30/12"

Oscillating table and podestal fans



Description

Oscillating table fan equipped with brushless DC motor.

- \bullet Grid, motor casing and support base in gray painted metal.
- Central frame, located between the front and rear grille, made of gray painted plastic material (ABS).
- Support rod in gray painted metal.
- \bullet Touch buttons with LED lights on the support rod, showing the set functions.
- \bullet Axial impeller directly coupled to a 4-speed DC (brushless) motor, designed to ensure safe and reliable operation.

 • Automatic horizontal oscillation (max angle 90°).
- Possibility of manual vertical adjustment of the fan body.
- Automatic switch-off timer, settable up to a maximum of 4 hours.
- 24V power supply with Italian plug and power cable with a useful length of 180 cm.

PER INFORMAZIONI / FOR INFORMATION

ITALY

Pre Sales:

prevendita@vortice-italy.com

After Sales:

postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF

IRELAND

Sales Dept:

sales@vortice.ltd.uk Technical Dept:

technical@vortice.ltd.uk

OTHER COUNTRIES

Sales Dept:

export@vortice-italy.com

After Sales:

after-sales@vortice-italy.com