

Standard Ballasts 18–58 W, 230/240/220 V

Lamp				Ballast									Capacitor				
Output	Type	Base	Current	Type	Ref. No.	Voltage	a	b	c	Weight	$\Delta t / \Delta t_{an}$	Energy efficiency	C _p	Current			
W			mA			V, Hz	mm	mm	mm	kg	K		μF	mA			
230 V, 50 Hz																	
26	TC-D/TC-T	G24d-3/GX24d-3	325	LN 18.131*	530941	230, 50	150	140	60	0.55	55/95	B1	3.5	140			
				LN 26.813*	509502	230, 50	110	100	45	0.41	55/145	B2	3.5	140			
				L 18.934*	534621	230, 50	150	140	45	0.43	70/150	—	3.5	140			
28	TC-DD	GR8/GR10q	320	LN 18.510*	164572	230, 50	155	140	92	0.80	40/65	B1	3.5	150			
				LN 18.131*	530941	230, 50	150	140	60	0.55	55/95	B1	3.5	150			
				L 18.934*	534621	230, 50	150	140	45	0.43	70/150	—	3.5	150			
32	TR	G10q	450	LN 36.570*	169779	230, 50	155	140	92	0.80	35/90	B2	4.0	220			
36	TC-F/TC-L	2G10/2G11	430	LN 36.570*	169779	230, 50	155	140	92	0.80	35/90	B1	4.5	210			
				LN 36.511*	164590	230, 50	155	140	92	0.80	35/95	B1	4.5	210			
				LN 36.130*	527191	230, 50	150	140	60	0.55	50/140	B2	4.5	210			
				LN 36.149*	529029	230, 50	150	140	60	0.55	55/150	B2	4.5	210			
				L 36.132*	535977	230, 50	150	140	45	0.43	65	—	4.5	210			
36/40	T-U/TR	2G13/G10q	430	LN 36.570*	169779	230, 50	150	140	92	0.80	35/90	B1	4.5	210			
				LN 36.149*	529029	230, 50	150	140	60	0.55	55/150	B2	4.5	210			
				L 36.132*	535977	230, 50	150	140	45	0.43	65	—	4.5	210			
38	TC-DD	GR10q	430	LN 36.570*	169779	230, 50	155	140	92	0.80	35/90	B1	4.5	210			
				LN 36.149*	529029	230, 50	150	140	60	0.55	55/150	B2	4.5	210			
				L 36.132*	535977	230, 50	150	140	45	0.43	65	—	4.5	210			
58	T-U	2G13	670	LN 58.568*	169389	230, 50	233	220	160	1.31	35/95	B1	7.0	320			
				LN 58.990*	509349	230, 50	190	180	110	0.95	50/130	B2	7.0	320			
				LN 58.116*	508186	230, 50	190	180	92	0.80	55/160	B2	7.0	320			
240 V, 50 Hz																	
18	TC-D/TC-T	G24d-2/GX24d-2	220	LN 18.418	164353	240, 50	85	75	34	0.28	60/130	B1	2.0	110			
				TC-F/TC-L	2G10/2G11	370	LN 18.507	164566	240, 50	155	140	92	0.80	35/60	B1	4.5	120
							LN 18.162	533043	240, 50	150	140	60	0.55	60/110	B2	4.5	120
	T-U	2G13	370	L 18.936*	534627	240, 50	150	140	45	0.43	70/140	—	4.5	120			
				LN 18.507	164566	240, 50	155	140	92	0.80	35/60	B1	4.5	120			
				LN 18.162	533043	240, 50	150	140	60	0.55	60/110	B2	4.5	120			
2x18	TC-F/TC-L	2G10/2G11	400	L 18.936*	534627	240, 50	150	140	45	0.43	70/140	—	4.5	120			
				LN 2x18.135	535778	240, 50	150	140	45	0.43	65	B1	4.0	210			
				LN 36.201	527196	240, 50	150	140	60	0.55	55/140	B1	4.0	210			
21	TC-DD	GR10q	260	LN 36.505	164555	240, 50	155	140	92	0.80	40/95	B1	4.0	210			
				LN 21.293	547145	240, 50	105	95	45	0.41	55	B1	3.0	120			
				LN 18.507	164566	240, 50	155	140	92	0.80	35/60	B1	4.5	150			
24	TC-F/TC-L	2G10/2G11	345	LN 18.162	533043	240, 50	150	140	60	0.55	60/110	B2	4.5	150			
				L 18.936*	534627	240, 50	150	140	45	0.43	70/140	—	4.5	150			
				LN 18.162	533043	240, 50	150	140	60	0.55	60/110	B1	4.5	150			
26	TC-D/TC-T	G24d-3/GX24d-3	325	LN 26.238	545405	240, 50	105	95	45	0.41	55/145	B2	3.5	140			
				LN 18.162	533043	240, 50	150	140	60	0.55	60/110	B1	4.5	150			
28	TC-DD	GR8/GR10q	320	LN 18.162	533043	240, 50	150	140	60	0.55	60/110	B1	3.5	150			
				L 18.936*	534627	240, 50	150	140	45	0.43	70/140	—	3.5	150			
32	TR	G10q	450	LN 36.505	164555	240, 50	155	140	92	0.80	40/95	B1	4.0	220			
36	TC-F/TC-L	2G10/2G11	430	LN 36.505	164555	240, 50	155	140	92	0.80	40/95	B1	4.5	210			
				LN 36.201	527196	240, 50	155	140	60	0.55	55/140	B2	4.5	210			
				L 36/40.443*	164438	240, 50	150	140	60	0.55	65/155	—	4.5	210			
36/40	T-U/TR	2G13/G10q	430	LN 36.505	164555	240, 50	155	140	92	0.80	40/95	B1	4.5	210			
				LN 36.201	527196	240, 50	150	140	60	0.55	55/140	B2	4.5	210			
				L 36/40.443*	164438	240, 50	150	140	60	0.55	65/155	—	4.5	210			
38	TC-DD	GR10q	430	LN 36.201	527196	240, 50	150	140	60	0.55	55/140	B2	4.5	210			
				L 36/40.443*	164438	240, 50	150	140	60	0.55	65/155	—	4.5	210			
58	T-U	2G13	670	LN 58.506	164560	240, 50	233	220	160	1.31	35/85	B1	7.0	320			
				LN 58.192	507936	240, 50	190	180	110	0.95	50/150	B2	7.0	320			
				LN 58.722	534252	240, 50	190	180	92	0.80	60/180	B2	7.0	320			

* Ballasts without CE marking for replacements or markets outside of the EU