

Standard Ballasts 18–58 W, 230/240/220 V

Lamp				Ballast									Capacitor	
Output	Type	Base	Current	Type	Ref. No.	Voltage	a	b	c	Weight	$\Delta t/\Delta t_{an}$	Energy efficiency	C _p	Current
W			mA			V, Hz	mm	mm	mm	kg	K		μF	mA
220 V, 50 Hz														
18	TC-F/TC-L	2G10/2G11	370	L18.933	534624	220,50	150	140	45	0.43	70/160	—	4.5	120
	T-U	2G13	370	L18.933	534624	220,50	150	140	45	0.43	70/160	—	4.5	120
2x18	TC-F/TC-L	2G10/2G11	400	L 36.158	530252	220,50	150	140	45	0.43	65	—	4.0	210
24	TC-F/TC-L	2G10/2G11	345	L18.933	534624	220,50	150	140	45	0.43	70/160	—	4.5	150
26	TC-D/TC-T	G24d-3/GX24d-3	325	L18.933	534624	220,50	150	140	45	0.43	70/160	—	3.5	140
28	TC-DD	GR8/GR10q	320	L18.933	534624	220,50	150	140	45	0.43	70/160	—	3.5	150
36	TC-F/TC-L	2G10/2G11	430	L 36.158	530252	220,50	150	140	45	0.43	65	—	4.5	210
36/40	T-U/TR	2G13/G10q	430	L 36.158	530252	220,50	150	140	45	0.43	65	—	4.5	210
38	TC-DD	GR10q	430	L 36.158	530252	220,50	150	140	45	0.43	65	—	4.5	210
58	T-U	2G13	670	L 58.625	164828	220,50	190	180	92	0.80	55/155	—	7.0	320
220 V, 60 Hz														
18	TC-D/TC-T	G24d-2/GX24d-2	220	L 181.602	164779	220, 60	85	75	34	0.32	45/110	—	2.0	110
	TC-F/TC-L	2G10/2G11	370	L 18.121	532149	220, 60	110	100	45	0.42	65/145	—	4.0	150
L 18.121				528582	220, 60	150	140	45	0.43	65/145	—	4.0	150	
L 18.249				538801	220, 60	150	140	34	0.32	75/140	—	4.0	150	
T-U	2G13	370	L 18.121	532149	220, 60	110	100	45	0.42	65/145	—	4.0	150	
			L 18.121	528582	220, 60	150	140	45	0.43	65/145	—	4.0	150	
			L 18.249	538801	220, 60	150	140	34	0.32	75/140	—	4.0	150	
2x18	TC-F/TC-L	2G10/2G11	400	L 36.120	509373	220, 60	150	140	45	0.43	60/170	—	4.0	210
24	TC-F/TC-L	2G10/2G11	345	L 18.121	532149	220, 60	110	100	45	0.42	65/145	—	4.0	190
				L 18.121	528582	220, 60	150	140	45	0.43	65/145	—	4.0	190
				L 18.249	538801	220, 60	150	140	34	0.32	75/140	—	4.0	190
26	TC-D/TC-T	G24d-3/GX24d-3	325	L 18.121	532149	220, 60	110	100	45	0.42	65/145	—	3.0	160
				L 18.121	528582	220, 60	150	140	45	0.43	65/145	—	3.0	160
				L 18.249	538801	220, 60	150	140	34	0.32	75/140	—	3.0	160
28	TC-DD	GR8/GR10q	320	L 18.121	532149	220, 60	110	100	45	0.42	65/145	—	3.0	155
				L 18.249	538801	220, 60	150	140	34	0.32	75/140	—	3.0	155
36	TC-F/TC-L	2G10/2G11	430	L 36.120	509373	220, 60	150	140	45	0.43	60/170	—	4.0	210
36/40	T-U/TR	2G13/G10q	430	L 36.120	509373	220, 60	150	140	45	0.43	60/170	—	4.0	220
38	TC-DD	GR10q	430	L 36.120	509373	220, 60	150	140	45	0.43	60/170	—	4.0	220
58	T-U	2G13	670	L 58.657	164870	220, 60	195	180	92	0.80	55/140	—	6.0	320

1

2

3

4

5

6

7

8

9

10