



Ballasts for HS and HI Lamps 250 to 600 W

Shape: 92x102 mm

For high pressure sodium lamps (HS), metal halide lamps (HI) and ceramic discharge lamps (C-HI)
Vacuum-impregnated with polyester resin
Screw terminals: 0.75–2.5 mm²
Protection class I
tw 130

Ballasts for pulse ignition system on request



Lamp			Ballast										Capacitor	
Output W	Type	Current A	Type	Ref. No.	Voltage AC V, Hz	a mm	b mm	c mm	Weight kg	Δt K	Power factor λ	Energy efficiency	C _P μF	I _N A
250	HS, HI	3.00	NaHj 250.003	179743	220, 50	133	120	44	3.53	70	0.41	EEl=A3	32	1.32
			NaHj 250.727*	178771	230, 50	133	120	44	3.53	70	0.39	EEl=A3	32	1.26
			NaHj 250.727	500976	240, 50	133	120	44	3.53	70	0.39	EEl=A3	32	1.21
			NaHj 250.011	500401	220, 60	133	120	44	3.53	65	0.43	A2	25	1.35
400	HS, HI	4.45	NaHj 400.006	179740	220, 50	148	135	68	5.20	70	0.44	A2	45	2.00
			NaHj 400.006	178790	230, 50	148	135	68	5.20	70	0.44	A2	45	1.95
			NaHj 400.737	500402	240, 50	148	135	68	5.20	75	0.43	A2	45	1.90
			NaHj 400.012	500403	220, 60	148	135	68	5.20	70	0.44	A2	40	2.00
	HI	3.50	J 400.027	505782	230/240, 50	148	135	68	5.20	60	0.45	A2	35	1.64/1.59
600	HS	6.20	NaH 600.010	179742	220, 50	173	160	96	6.80	70	0.44	A2	65	2.90
			NaH 600.005	533484	230/240, 50	173	160	96	6.80	70	0.44	A2	65	2.90/2.85
			NaH 600.140	529560	220, 60	173	160	96	6.80	65	0.46	A2	55	3.00

* Ballasts without CE marking for replacements or markets outside of the EU

With Thermal Cut-out

Thermal cut-out with automatic reset

Lamp			Ballast										Capacitor	
Output W	Type	Current A	Type	Ref. No.	Voltage AC V, Hz	a mm	b mm	c mm	Weight kg	Δt K	Power factor λ	Energy efficiency	C _P μF	I _N A
250	HS, HI	3.00	NaHj 250.727*	500969	230/240, 50	133	120	44	3.53	70	0.39	EEl=A3	32	1.26/1.21
			NaHj 250.011	508744	220, 60	133	120	44	3.46	65	0.43	A2	25	1.35
400	HS, HI	4.45	NaHj 400.737	179424	230/240, 50	148	135	68	5.20	70/75	0.43	A2	45	1.95/1.90
			HI	3.50	J 400.027	509613	230/240, 50	148	135	68	5.20	60	0.45	A2
	HS, HI	4.45	NaHj 400.012	508741	220, 60	148	135	68	5.20	70	0.44	A2	40	2.00
600	HS	6.20	NaH 600.005	179454	230/240, 50	173	160	96	6.80	70	0.44	A2	65	2.90/2.85

* Ballasts without CE marking for replacements or markets outside of the EU